



S4/i S35 T2.0 镜头 | 基础参数规格

产品规格	12mm	14mm	16mm	18mm	21mm	25mm	27mm	32mm	35mm
光圈	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22
光圈刻度的旋转角度	96°	96°	96°	96°	96°	96°	96°	96°	95°
最小标记物体距离	225 mm	225 mm	225 mm	250 mm	250 mm	250 mm	250 mm	325 mm	350 mm
	9in	9in	9in	9in	9in	9in	10 in	12 in	14 in
角度旋转到MOD终点	270°	300°	270°	300°	270°	300°	270°	300°	300°
从镜头前端到 PL 卡口的长度	126 mm	122 mm	126 mm	107 mm	107 mm	107 mm	111 mm	123 mm	127 mm
	5 in	4.8 in	5 in	4.2 in	4.2 in	4.2 in	4.4 in	4.8 in	5 in
最大前端直径	156 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm
	6.1in	4.3in	4.3in	4.3in	4.3in	4.3in	4.3 in	4.3 in	4.3 in
30 毫米图像对角线时 S35 格式的最大对角线视角	103°	94°	86°	80°	71°	62°	58°	50°	46°
总重量 (带 PL 镜头卡口)	3 kg	2.2 kg	2.4 kg	1.7 kg	2.0 kg	1.6 kg	1.6 kg	1.8 kg	1.9 kg
	6.5 lbs	4.8 lbs	5.4 lbs	3.8 lbs	4.4 lbs	3.5 lbs	3.5 lbs	4 lbs	4.2 lbs
前端滤镜螺纹	N/A	N/A	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75

Continued on next page →

最大格式覆盖范围	直径 30 毫米 (Super35 格式)
焦点刻度	双焦点刻度 - 英制和公制, 刻度标记从无穷远到 MOD
焦点驱动齿轮	140 齿 0.8 公制模块
光圈刻度	两个相对的线性 T 形刻度 - 标有全档和三档
光圈驱动齿轮	134 齿 0.8 公制模数
镜头卡口	PL



S4/i S35 T2.0 镜头 | 基础参数规格

产品规格	40mm	50mm	65mm	75mm	100mm	135mm	150mm	180mm	300mm
光圈	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2.8 - T22
光圈刻度的旋转角度	94°	93°	92°	92°	91°	92°	92°	94°	78°
最小标记物体距离	450 mm	550 mm	700 mm	800 mm	950 mm	850 mm	1,050 mm	1,300 mm	2,100 mm
	16 in	20 in	2 ft 3 in	2 ft 6 in	3 ft	2 ft 9 in	3 ft 6 in	4 ft 3 in	7 ft
角度旋转到MOD终点	300°	300°	300°	300°	300°	340°	320°	320°	320°
从镜头前端到 PL 卡口的长度	135 mm	120 mm	122 mm	120 mm	136 mm	184 mm	157 mm	185 mm	202 mm
	5.3 in	4.7 in	4.8 in	4.7 in	5.4 in	7.3 in	6.2 in	7.3 in	8 in
最大前端直径	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	125 mm	136 mm	136 mm
	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.9 in	5.3 in	5.3 in
30 毫米图像对角线时 S35 格式的最大对角线视角	41°	34°	26°	22°	17°	13°	11.5°	9.5°	5.7°
总重量 (带 PL 镜头卡口)	2 kg	1.5 kg	1.6 kg	1.7 kg	2 kg	2.2 kg	3.5 kg	4.3 kg	4.7 kg
	4.4 lbs	3.3 lbs	3.5 lbs	3.8 lbs	4.4 lbs	4.9 lbs	7.7 lbs	9.4 lbs	10.3 lbs
前端滤镜螺纹	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M120 x 1.0	M131 x 1.0	M131 x 1.0

最大格式覆盖范围	直径 30 毫米 (Super35 格式)
焦点刻度	双焦点刻度 - 英制和公制, 刻度标记从无穷远到 MOD
焦点驱动齿轮	140 齿 0.8 公制模块
光圈刻度	两个相对的线性 T 形刻度 - 标有全档和三档
光圈驱动齿轮	134 齿 0.8 公制模数
镜头卡口	PL