



SP3 | 基础参数规格

Specifications	18mm	25mm	32mm	50mm	75mm	100mm
光圈	T2.4 - T16	T2.4 - T16	T2.4 - T16	T2.4 - T16	T2.4 - T16	T2.4 - T16
光圈刻度的旋转角度	78°	78°	78°	78°	78°	78°
最近标记对焦距离	250 mm 10 in	250 mm 10 in	350 mm 13 in	500 mm 20 in	800 mm 3 ft	800 mm 3 ft
距镜头前端最近对焦距离	79.73 mm 3.14 in	139 mm 5.5 in	223 mm 8.8 in	394 mm 15.5 in	689 mm 27.1 in	663 mm 26.1 in
角度旋转到MOD终点	160°	160°	160°	160°	160°	160°
镜头总长度 (E卡口)	109 mm 4.29 in	98 mm 3.85 in	94 mm 3.7 in	94 mm 3.7 in	98 mm 3.85 in	124 mm 4.88 in
最大前端直径	82 mm 3.29 in	64 mm 2.52 in	64 mm 2.52 in	64 mm 2.52 in	64 mm 2.52 in	82 mm 3.22 in
全画幅格式对角线视野	99.72°	81°	69°	47°	32°	25°
S35格式对角线视野	81.65°	62°	50°	34°	22°	17°
总重量 (含镜头卡口)	688 g 1.51 lbs	575 g 1.27 lbs	520 g 1.15 lbs	500 g 1.10 lbs	520 g 1.15 lbs	690 g 1.52 lbs
前端滤镜螺纹	M77 x 0.75	M58 x 0.75	M58 x 0.75	M58 x 0.75	M77 x 0.75	

最大格式覆盖范围	全画幅, 成像圈 46.3 mm
焦点刻度	双焦点非线性刻度 - 英制和公制 - 刻度范围从无穷远到 MOD
焦点驱动齿轮	83齿 0.8 公制模数
光圈刻度	非线性, 整数与1/3刻度
光圈驱动齿轮	83齿 0.8 公制模数
卡口	E, RF, L, M (RF-卡口, L-卡口和 M-卡口 单独出售)

镜头附带已安装的E卡口, 并且每个镜头可额外免费订购一个卡口 (RF卡口、L卡口或M卡口), 具体操作请按照包装内的说明在Cooke网站。